





TRITURADORES SÉRIE FT8



MODELO	LARGURA TRABALHO	POTÊNCIA EXIGIDA	PESO Kg			
FT8-90	89 cm	20-30 HP	255	24	8	
FT8-110	109 cm	25-35 HP	300	30	10	
FT8-130	129 cm	30-40 HP	330	36	12	
FT8-150	149 cm	40-50 HP	360	42	14	
FT8-180	177 cm	45-55 HP	410	48	16	
FT8-200	206 cm	50-60 HP	450	54	18	

TRITURADORES SÉRIE FT8s (DESLOCÁVEL)

MODELO	LARGURA TRABALHO	POTÊNCIA EXIGIDA	PESO Kg			
FT8s-110	109 cm	25-35 HP	320	30	10	
FT8s-130	129 cm	30-40 HP	350	36	12	
FT8s-150	149 cm	40-50 HP	380	42	14	
FT8s-180	177 cm	45-55 HP	420	48	16	
FT8s-200	206 cm	50-60 HP	460	54	18	

OPCIONAIS	
Deslocamento lateral hidráulico FT8s	
Grade posterior FT8-90	
Grade posterior FT8/8s-110	
Grade posterior FT8/8s-130	
Grade posterior FT7/8s-150	
Grade posterior FT7/8/8s-180	
Grade posterior FT7/8/8s-200	
Par de patins	
Suplemento corrente de protecção anterior (por metro)	
Cardan	
Suplemento para montagem frontal FT8	
Suplemento para versão reversível FT8s	