





**TRITURADORES SÉRIE FT12s
(DESLOCÁVEL)**



MODELO	LARGURA TRABALHO	POTÊNCIA EXIGIDA	PESO Kg			
FT12s-150	149 cm	30-40 HP	530	42	14	
FT12s-180	177 cm	40-50 HP	560	48	16	
FT12s-200	206 cm	50-60 HP	600	54	18	
FT12s-230	229 cm	60-70 HP	670	66	22	
FT12s-250	249 cm	70-80 HP	710	72	24	
FT12s-280	282 cm	80-90 HP	760	78	26	

**TRITURADORES SÉRIE FT12sr
(DESLOCÁVEL E REVERSÍVEL)**

MODELO	LARGURA TRABALHO	POTÊNCIA EXIGIDA	PESO Kg			
FT12sr-150	149 cm	30-40 HP	530	42	14	
FT12sr-180	177 cm	40-50 HP	560	48	16	
FT12sr-200	206 cm	50-60 HP	600	54	18	
FT12sr-230	229 cm	60-70 HP	670	66	22	
FT12sr-250	249 cm	70-80 HP	710	72	24	
FT12sr-280	282 cm	80-90 HP	760	78	26	

OPCIONAIS	
Deslocamento hidráulico	
Grade posterior FT12-150	
Grade posterior FT12-180	
Grade posterior FT12-200	
Grade posterior FT12-230	
Grade posterior FT12-250	
Grade posterior FT12-280	
Par de patins	
Suplemento corrente de protecção anterior (por metro)	
Suplemento par de rodas posteriores em lugar do rolo	
Rolo de maior diâmetro	
Cardan	
Cardan para modelos FT12-250/280	